

Appl. No.: 10/069,140
Filed: February 22, 2002
Page 2

Amendments to the Claims:

1.-24. (cancelled)

25. (previously presented) A light source comprising
a bulb,

a filament mounted within said bulb and which has an
arcuate configuration when viewed in plan so as to define a
space within the bulb which is at least partially enclosed by
the filament,

an electrical heating device for heating the filament
whereby the filament can be heated to cause the emission of
visible light and heat radiation, said heating device
including an incandescent heating element positioned within
said space for indirectly heating the filament, and

wherein said heating device further comprises an
electrical circuit connecting the filament and the heating
element in series.

26. (previously presented) The light source of Claim 25
wherein said heating device further includes a pair of
electrical contacts which are electrically connected to said
heating element.

27. (previously presented) The light source of Claim 25
wherein said filament is in the form of at least a portion of
a cylindrical jacket.

28. (previously presented) The light source of Claim 27
wherein the at least a portion of a cylindrical jacket
includes a lengthwise extending opening.

Appl. No.: 10/069,140
Filed: February 22, 2002
Page 3

29. (previously presented) The light source of Claim 27 wherein the at least a portion of a cylindrical jacket extends for at least 180° when viewed in plan and defines a diameter which is only slightly smaller than a diameter defined by the bulb.

30. (previously presented) The light source of Claim 25 wherein the bulb defines a longitudinal axis, with the filament being configured to define a coaxial center axis.

31. (previously presented) The light source of Claim 25 wherein the bulb defines a longitudinal axis and wherein the heating element is in the form of a helical coil which is disposed coaxially along the longitudinal axis.

32. (previously presented) The light source of Claim 25 wherein the filament comprises a sintered metal selected from the group consisting of tungsten, rhenium, tantalum, zirconium, niobium, and mixtures thereof.

33. (previously presented) The light source of Claim 25 wherein the filament includes a nonmetal.

34. (previously presented) The light source of Claim 25 wherein the filament comprises a metal selected from the group consisting of tantalum carbide, rhenium carbide, niobium carbide, zirconium carbide and mixtures thereof.

35. (previously presented) The light source of Claim 25 wherein the heating element essentially comprises tungsten.

Appl. No.: 10/069,140
Filed: February 22, 2002
Page 4

36. (previously presented) The light source of Claim 25 wherein the bulb includes an inner surface which includes a mirror coating.

37. (previously presented) The light source of Claim 36 wherein the mirror coating comprises a dielectric multilayer coating.

38. (previously presented) The light source of Claim 37 wherein the dielectric multilayer coating is spectrally selective so as to substantially reflect the heat radiation emitted by the filament while substantially transmitting the emitted visible light.

39. (previously presented) The light source of Claim 25 wherein the bulb is at least partially filled with an inert gas and/or a halogen gas.

40. (previously presented) The light source of Claim 25 wherein the bulb is at least partially filled with a halogen gas which contains bromine and/or iodine.

41. (previously presented) The light source of Claim 25 wherein the filament and/or the heating element are coated with a coating material which has a higher melt temperature than the material upon which it is coated.

42. (previously presented) The light source of Claim 41 wherein the coating material includes a carbide selected from the group consisting of tantalum carbide, rhenium carbide, niobium carbide, zirconium carbide, and mixtures thereof.

Appl. No.: 10/069,140
Filed: February 22, 2002
Page 5

43.-44. (cancelled)